

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
24 July 2003 (24.07.2003)

PCT

(10) International Publication Number
WO 03/059768 A1

(51) International Patent Classification⁷: **B65D 41/04**

SD, SG, SL, TJ, TM, TN, TT, TZ, UA, UG, US, UZ, VC,
VN, YU, ZA, ZM, ZW.

(21) International Application Number: PCT/GR03/00001

(22) International Filing Date: 15 January 2003 (15.01.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20020100015 16 January 2002 (16.01.2002) GR
20020100016 16 January 2002 (16.01.2002) GR

(71) Applicant and

(72) Inventor: PAIRIS, Dimitrios [GR/GR]; 10-12 Dimitriou
Poliorkitou Str., GR-136 71 Thrakomkedones Attikis (GR).

(74) Agent: TSIBRIS, Michael; 34 Asklipiou Str., GR-106 80
Athens (GR).

(81) Designated States (national): AE, AG, AL, AM, AU, AZ,
BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ,
DM, DZ, EC, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP,
KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LV, MA, MD,
MG, MK, MN, MW, MX, NZ, OM, PH, RO, RU, SC,

(84) Designated States (regional): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI,
SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


- as to the identity of the inventor (Rule 4.17(i)) for all designations
- as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii)) for all designations
- of inventorship (Rule 4.17(iv)) for US only

Published:

- with international search report
- before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: PLASTIC CLOSING CAP WITH SEALING RING



(57) Abstract: A closing cap moulded in one piece from a plastics material for sealing a container with a threaded neck has a top plate (3), an annular skirt (4) with an internal screw thread (5) adapted to cooperate with the threaded container neck (2), and an integrally moulded deformable annular sealing ring (6) extending downwardly from an inner surface of said top plate (3) and spaced radially inwardly of the annular skirt (4), wherein when the closing cap (1) is screwed onto the container neck (2), the sealing ring (6) is deformed outwardly and is fully conformed to the outer surface of the container neck (2) without being clamped between the container neck (2) and the annular skirt (4) and without being pressed against the annular skirt (4).

WO 03/059768 A1

5

PLASTIC CLOSING CAP WITH SEALING RING

TECHNICAL FIELD OF THE INVENTION

10 The present invention relates to a plastic closing cap for a container with an annular sealing ring.

BACKGROUND OF THE INVENTION

15 Container closures moulded in one piece from a plastic material including downwardly depending seals are well known in the art. The purpose of these arrangements is to enable a cap to be easily screwed onto a container neck such that the edge of the container neck seals against the underside of the top plate of the cap, while the sealing ring is pressed
20 into firm sealing engagement with the edge of the container neck.

In the case of containers made of plastics material it can certainly happen that the edge of the container neck has
25 suffered minor damage, deformation and/or irregularities caused during the manufacturing procedure, and which are sufficient to have a negative effect on the sealing engagement between the edge of the container neck and sealing elements of the cap.
30 Thus, a deteriorated seal in the case of bottles for carbonated drinks can have the result that gas escapes from the bottle and after a few days of storage the drink has lost its carbon dioxide and is tasteless.

35 The known closures therefore still do not guarantee absolutely sealing integrity in the event of minor damage or deformation of the edge of the container neck.

40 In addition, caps when applied to plastic containers for sterilized beverage e.g. milk or dairy products, must also meet rigid requirements to prevent contamination and the overall cap structure must be leak-proof. In order to provide a liquid-tight seal it is, therefore, known to use either a sealing laminated membrane on the opening of the
45 container or a separate liner inside of the cap.

However, these arrangements are characterized by higher manufacturing and/or recycling costs while cannot guarantee
50 reliable sealing integrity.

SUMMARY OF THE INVENTION

5 It is, therefore, an object of the present invention to provide an improved plastic closing cap, which overcomes the deficiencies of the prior art and ensures reliably the sealing function and prevents leaks in the event of minor
10 damage or deformation of the container neck.

A further aspect of the present invention is to provide a closing cap particular useful for sterilized products such as milk or dairy products which provides easy opening and
15 reclosing of the container and effectively sealing prior to and after reclosing.

In accordance with the above objects of the present invention, a closing cap moulded in one piece from a
20 plastics material for sealing a container with a threaded neck is provided comprising a top plate which is substantially in the form of a circular disc, a substantially cylindrical peripheral portion extending downwardly from said top plate, said peripheral portion having an internal
25 screw thread adapted to cooperate with the threaded container neck, an integrally moulded deformable sealing ring extending downwardly from an inner surface of said top plate and spaced radially inward of the substantially cylindrical peripheral portion, wherein when said closing
30 cap is applied onto the threaded container neck, said sealing ring is adapted to radially deform outwardly and seal at least substantially along the outer surface of the container neck by virtue of the elastic return forces without being clamped between the container neck and the
35 substantially cylindrical peripheral portion and without being pressed against the substantially cylindrical peripheral portion.

Further preferred embodiments of the present invention are
40 defined in dependent claims 2 to 17.

The closing cap of the invention is ergonomic by offering compactness, and it adapts very easily to any container necks.

45 In the closed position it ensures perfect sealing. The cap is also able to retain a liquid-tight seal after a period of time due to its configuration in conjunction with its material's characteristics.

Operations of assembling the cap together on the neck of the
50 container is quick and very easy.

5 Other objects and advantages of the present invention will become apparent to those skilled in the art in view of the following detailed description taken in conjunction with the accompanying drawings, wherein like reference numbers refer to similar parts throughout the drawings, and wherein:

10 BRIEF DESCRIPTION OF THE DRAWINGS

15 Figs. 1A and 1B show a perspective view, partially broken away, of a closing cap according to the present invention applied to the container prior to, and after formation of a seal;

20 Figs. 2A and 2B show a perspective view, partially broken away, of a second alternative closing cap according to the present invention applied to the container prior to, and after formation of a seal;

25 Figs. 3A and 3B show a perspective view, partially broken away, of a third alternative closing cap according to the present invention applied to the container prior to, and after formation of a seal;

30 Figs. 4A and 4B show a perspective view, partially broken away, of another alternative closing cap according to the present invention applied to the container prior to, and after formation of a seal;

35 Figs. 5A and 5B show a partial cross-sectional view of an alternative closing cap according to the present invention in place on a container prior to, and after removal of the laminated disc; and

40 Fig. 6A and 6B show a partial cross-sectional view of a further alternative closing cap according to the present invention in place on a container prior to, and after removal of the laminated disc.

DETAILED DESCRIPTION OF THE INVENTION

45 Referring first to Figure 5A of the drawings, the closing cap 1 is moulded in one piece from a resilient plastics material and has a top plate 3 in the shape of a circular disc and an annular skirt 4 peripherally downwardly depending therefrom. The annular skirt 4 has an internal screw thread 5. On the inner surface of the top plate 3
50 extending downwardly there is an integrally moulded thin,

5 deformable annular sealing ring 6 of uniform thickness which
is of substantially cylindrical construction. In addition,
the sealing ring 6 is disposed at a position spaced radially
inwardly of the annular skirt 4, and concentric with said
annular skirt. Said sealing ring 6 has a length such as to
10 permit its portion adjoining its free edge to extend along
the upper outer surface of the container neck 2. The sealing
ring 6 is made of the same plastic material as the cap 1 and
preferably has a thickness of equal or less than 0.8mm.

15 A container has an annular neck 2 with an external thread
formed thereon.
In accordance with one aspect of the present invention the
closing cap is adapted for use with a container, which is a
thin-walled light weight blow-molded plastic bottle (e.g.
for milk or dairy products) provided with an externally
20 screw-threaded neck 2. The container neck 2 has above its
threads an upwardly and inwardly directed portion 8 which is
tapered (e.g. frusto-conically) and may have a substantially
radially inwardly directed rim 9 for engagement with a stop
means 7 of the closing cap referred to below.

25 In use, as depicted in Figs.1A and 1B, the closing cap 1 is
applied to the container neck 2 so that the top of the
container neck moves upwardly as in Figure 1A to adopt the
position shown in Figure 1B.

30 As it does so the sealing ring 6 first comes into contact
with the outer surface of the container neck 2 while the
closing cap 1 is being rotated during the capping operation.
Further rotation of the closing cap 1 relative to the
container neck 2 causes the container neck 2 to move
35 upwardly relative to the closing cap 2 to adopt the position
shown in Figure 1B.

On the inner surface of the top plate, the sealing ring 6 is
disposed at a radius approximately equal to the radial
distance of the middle of the tapered portion 8 of the
40 container neck 2. Therefore, during the capping operation
the sealing ring 6 is being urged away by the tapered
portion 8 of the container neck 2 and thus it is deformed
radially outwardly, and lies against the outer surface of
the tapered portion 8 of the container neck, and has a
45 sufficient length in contact with it.

Hence, the sealing ring 6 is fully conformed to the outer
surface of the container neck 2 by virtue of its elasticity
without being clamped between the container neck 2 and the
annular skirt 4 and without being pressed against the skirt
50 4.

5 In this condition an effective tight seal is formed between the outer surface of the tapered portion 8 of the container neck 2 and the inner surface of the sealing ring 6. Moreover, due to the elastic return forces which occur in that case and the deformation of the sealing ring 6 in conjunction with the resilience of the plastics material, 10 said seal is maintained despite relaxation.

15 At the same time, because of this radial displacement of the sealing ring 6, there is a pivotal force applied to the inner surface of the top plate 3 which tends to resist doming in conjunction with the stop means 7 of the cap referred to below.

20 Referring now to Figures 2A and 2B of the drawings, another modification of the present invention is shown in which the sealing ring is L-shaped and sealing integrity is afforded by virtue of engagement of the short side of the L-shaped sealing ring, which is parallel to the top plate of the cap, 25 with the upper portion (tapered portion) of the container neck, wherein said short side is displaced inwardly and is then clamped between the outside surface of the container neck and the long side of the L-shaped sealing ring.

30 Figs. 3A and 3B show another modification of the invention in which the sealing ring is attached to the annular skirt above its internal threads and is substantially parallel to the top plate of the cap.

35 Figures 4A and 4B show a further modification of the present invention in which the sealing ring is attached to the inner surface of the top plate of the cap at a position spaced radially inwardly of the annular skirt and extends downwardly and inwardly (conical) from the top plate of the cap. 40

Arrangements of the foregoing type are used with a further main feature of the invention shown in Figures 1 to 6, i.e. the stop means 7.

45 Figs. 5A and 5B show an alternative modification for use in cases where there is a laminated disc 10 sealed on the container opening.

The laminated disc is attached to and sealed on the containers by means of a plastic heat shrinkable tube which 50 insures a tight sealing engagement about the container opening. This arrangement offers many advantages, e.g. high

shapping nature and high-temp resistance, tight sealing and
5 better fineness.

The stop means 7 is a shallow ring which extends downwardly
from the inner surface of the top plate 3. It is disposed
radially inwardly of the sealing ring 6, and has an external
10 diameter which is slightly smaller than the inner diameter
of the inwardly directed rim 9 of the container neck 2,
namely slightly smaller than the container opening.
The stop means is further provided with a tapering conical
tip.

15 As shown in Fig.5A, during the capping procedure, the
laminated disc 10 at the region of the rim portion 9 of the
container neck 2 comes into contact with the tapering tip of
the stop means 7 which has the effect of limiting the
20 upwardly movement of the container neck 2. In this condition
the closing cap 1 is screwed onto the container neck 2, the
sealing ring 6 is not deformed and a liduid-tight seal is
provided by the laminated disc 10.

25 Once the container has been opened and the laminated disc 10
has been removed, the reclosing of the container is achieved
in that the closing cap 1 is further rotated, and due to the
relative movement between the container neck 2 and the cap
1, the stop means 7 adopts the position shown in Figure 5B.
30 Only just during this reclosing procedure the sealing ring 6
comes into contact with the tapered portion 8 of the
container neck 2 and is thereby deformed.

Because the stop means 7 is intended essentially and
35 primarily as a restriction and secondly as a seal, the main
sealing effect also in this modification is to be found
between the outer surface of the tapered portion 8 of the
container neck 2 and the inner surface of the sealing ring
6.

40 Further, because the stop means 7 is disposed in-board of
the sealing ring 6, it tends to strengthen the central
portion of the top plate 3. This resists doming.

45 It will thus be seen that during reclosing of the cap 1 to
the container neck 2, the outer surface of the tapered
portion 8 of the container neck 2 first comes into contact
with the sealing ring 6 thereby causing effective sealing.

50 It will also be appreciated that by virtue of the relative
thickness of the flexible sealing ring 6 taken with the

effects of the stop means 7, a more effective seal is provided than previously.

5

The stop means 7 and the stiffness of the top plate 3 together result in that the effects of doming upon the sealing ring 6 are reduced thus ensuring that the sealing ring 6 does not get pulled out of sealing engagement with the container neck 2.

10

Further, the stop means 7 acts as a stiffening rib and may be continuous or discontinuous.

15

The arrangement shown in Figures 6A and 6B is similar to that in Figures 5A and 5B, but in Figs. 6A and 6B the stop means 7 is an annular disc depending from the inner surface of the top plate 3 of the cap and is generally trapezoidal in cross section, decreasing in a direction downwardly and away from the the top plate.

20

The inventive closing caps are preferably made by injection moulding of polypropylene or high density polyethylene plastics materials.

25

The stop means is intended to have sealing properties but needs to be used in conjunction with a primary seal for example as hereinbefore set forth.

30

The closing cap is designed to be fitted onto a glass or plastic container, such as a soft drink bottle. It should be noted that the container can hold various liquids including, but not limited to, dairy products, a carbonated beverage, a non-carbonated liquid or a vaporized product.

35

Closures of this type may be produced, preferably by injection moulding, with or without tamper evident band. Preferably the skirt terminates in a plurality of frangible bridges supporting a tamper evident band for cooperation with a plain security band on the outer neck portion of the container neck in the usual way.

40

The skirt is preferably provided with external knurling or vertical ribbing to improve manual grip. The thickness of the sealing ring may be preferably more than 0.80mm.

45

While preferred embodiments have been shown and described obviously minor modifications in design and construction can be effected in the invention without departing from the spirit and scope thereof, as defined in the appended claims.

50

CLAIMS

- 5 1. A closing cap moulded in one piece from a plastics material for sealing a container with a threaded neck comprising:
a top plate (3) which is substantially in the form of a circular disc;
10 a substantially cylindrical peripheral portion (4) extending downwardly from said top plate (3), said peripheral portion having an internal screw thread (5) adapted to cooperate with the threaded container neck (2);
15 an integrally moulded deformable annular sealing ring (6) extending downwardly from an inner surface of said top plate (3) and spaced radially inward of the substantially cylindrical peripheral portion (4), wherein when said closing cap (1) is applied onto the threaded container neck (2), said sealing ring (6) is adapted to radially deform
20 outwardly and seal at least substantially along the outer surface of the container neck (2) by virtue of the elastic return forces without being clamped between the container neck (2) and the substantially cylindrical peripheral portion (4) and without being pressed against said
25 substantially cylindrical peripheral portion (4).
2. The closing cap according to claim 1, wherein said sealing means (6) is substantially cylindrical.
- 30 3. The closing cap according to claim 1, wherein said sealing means (6) is L-shaped.
4. The closing cap according to any preceding claim, wherein said sealing means (6) has a uniform thickness of equal or
35 less than 0.80mm.
5. The closing cap according to any preceding claim, wherein said outer surface of the container neck (2) has, above its threads, an upwardly and inwardly directed tapered portion
40 (8) and a substantially radially inwardly directed rim (9) and said sealing ring (6) is disposed at a radius approximately equal to the radial distance of the middle of the tapered portion (8) of the container neck (2).
- 45 6. The closing cap according to claim 6, wherein said sealing ring (6) is deformed radially outwardly by the tapered portion (8) of the container neck (2) and is fully conformed to the outer surface of the container neck (2) by virtue of its elasticity without being pressed against the
50 substantially cylindrical peripheral portion (4).

7. The closing cap according to any preceding claim further comprising a continuous or discontinuous stop means (7) extending downwardly from the inner surface of said top plate (3) and disposed radially inwardly of said deformable sealing ring (6).
8. The closing cap according to claim 8, wherein said stop means (7) has an external diameter which is slightly smaller than an inner diameter of the substantially radially inwardly directed rim (9) of the container neck (2).
9. The closing cap according to any preceding claim, wherein said stop means (7) is adapted to limit the upwardly movement of the container neck (2).
10. The closing cap according to any preceding claim, wherein said stop means (7) is adapted to be inserted in the opening of the container neck (2) after removal of the sealing laminated disc (10).
11. The closing cap according to any preceding claim, wherein said sealing ring (6) only just during the reclosing procedure and after removal of the laminated disc (10) first comes into contact with the tapered portion (8) of the container neck (2) and is thereby deformed.
12. The closing cap according to any preceding claim, wherein said stop means (7) is a shallow ring with a tapering conical tip.
13. The closing cap according to any preceding claim, wherein said stop means (7) is an annular disc.
14. The closing cap according to any preceding claim, wherein said substantially cylindrical peripheral portion (4) has at its distal end a tamper evident band for cooperation with a security band on the outer neck portion of the container neck(2).
15. The closing cap according to any preceding claim, wherein said substantially cylindrical peripheral portion (4) is provided with external knurling.
16. The closing cap according to any preceding claim, wherein said closing cap (1) is made by injection moulding.
17. An assembly of a container having a threaded neck and a closing cap (1) according to any one of the preceding claims.

1/6




FIG. 1A




FIG. 1B




FIG. 2A




FIG. 2B




FIG. 3A




FIG. 3B




FIG. 4A




FIG. 4B




FIG. 5A




FIG. 5B




FIG. 6A




FIG. 6B

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 4 531 649 A (SHULL ROBERT W) 30 July 1985 (1985-07-30) column 2, line 8 -column 3, line 5; figures 7,8 ----	1,15,17
X	EP 1 092 639 A (CROWN CORK & SEAL TECH CORP) 18 April 2001 (2001-04-18) column 6, line 13 - line 17; figure 4 ----	1,3,17
Y	US 6 126 027 A (THOMPSON NIGEL) 3 October 2000 (2000-10-03) column 3, line 5 - line 61; figures 1,2 ----	8,14,15
Y	US 5 158 195 A (THOMPSON MORTIMER S) 27 October 1992 (1992-10-27) column 11, line 25 - line 51; figures 45-47 ----	4
A	GB 2 311 283 A (LAWSON MARDON) 24 September 1997 (1997-09-24) page 3 -page 4; figure -----	1-17

A. CLASSIFICATION OF SUBJECT MATTER
 IPC 7 B65D41/04

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

 Minimum documentation searched (classification system followed by classification symbols)
 IPC 7 B65D

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, PAJ

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 489 036 A (ARKINS THOMAS D) 6 February 1996 (1996-02-06)	1,2,5-7, 9,12,16, 17
Y	column 3 -column 6; figures 8,9	4,8,14, 15
X	US 5 449 078 A (AKERS EDWARD G) 12 September 1995 (1995-09-12) column 2, line 29 -column 3, line 27; figures 6,7	1,2,5-7, 13,15,17
X	US 4 637 519 A (SANTOSTASI PAUL A ET AL) 20 January 1987 (1987-01-20) column 5, line 44 -column 7, line 5; figure 1	1,6,7, 9-11,14, 17
	--- -/--	

☒ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

*** Special categories of cited documents :**

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

G document member of the same patent family

Date of the actual completion of the international search

5 May 2003

Date of mailing of the international search report

13/05/2003

Name and mailing address of the ISA

 European Patent Office, P.B. 5818 Patentlaan 2
 NL - 2280 HV Rijswijk
 Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
 Fax: (+31-70) 340-3016

Authorized officer

Fitterer, J

PCT/GR 03/00001

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5158195	A		AT 126494 T	15-09-1995
			AT 191198 T	15-04-2000
			AU 592612 B2	18-01-1990
			AU 6772687 A	30-06-1987
			BR 8607033 A	01-12-1987
			CA 1330779 A1	19-07-1994
			DE 3650370 D1	21-09-1995
			DE 3650370 T2	18-01-1996
			DE 3650743 D1	04-05-2000
			DK 418287 A	11-08-1987
			EP 0254729 A1	03-02-1988
			EP 0661216 A1	05-07-1995
			JP 2813146 B2	22-10-1998
			JP 7285565 A	31-10-1995
			JP 2602516 B2	23-04-1997
			JP 63502265 T	01-09-1988
			NO 873343 A	09-10-1987
			WO 8703561 A1	18-06-1987
			AT 102887 T	15-04-1994
			AU 595278 B2	29-03-1990
			AU 6738187 A	30-06-1987
			BR 8607032 A	01-12-1987
			CA 1330778 A1	19-07-1994
			DE 3689726 D1	21-04-1994
			DE 3689726 T2	27-10-1994
			DK 411487 A	07-08-1987
			EP 0248890 A1	16-12-1987
			JP 7005134 B	25-01-1995
			JP 63502266 T	01-09-1988
			NO 873344 A	09-10-1987
			WO 8703560 A1	18-06-1987
GB 2311283	A	24-09-1997	CA 2249302 A1	25-09-1997
			DE 69703835 D1	08-02-2001
			DE 69703835 T2	31-05-2001
			EP 0889835 A1	13-01-1999
			ES 2154894 T3	16-04-2001
			WO 9734814 A1	25-09-1997